

H-POS

Terminal Punto de Venta ideal para espacios reducidos.

Altas prestaciones en espacio reducido, con componentes modulares de última tecnología, completamente intercambiables con el modelo Z-POS y con otros productos AdvanPOS, utilizando sistemas de montaje y anclaje sin cableados, de práctico manejo.



Especificaciones

Sistema	CPU-Intel P4 Processor	Celeron M 1,5 Ghz. Processor Pentium M (PGA) 1.3Ghz ~ 2.0 Ghz. Celeron M LV / ULV BGA Processor
	Cache Memory	2nd Level depend on CPU
	System Chipset	Intel 915GM+ICH6
	System Memory	1 GB. (256 MB to 2 GB.)
	Compact Flash	Support Compact Flash Card
	HDD Driver	120 GB. (Built-in 2,5" SATA HDD bay)
	Audio	Integrated stereo (2W + 2W) speakers
	Optional UPS	Battery Pack (5 minutes run time after power loss)
	Construction	Magnesium-Aluminum & Aluminum Die-casting Housing
	O / S Support	Win2000, XP Pro, XP Embedded, WEPOS and Linux.

COLORS



Pantalla Principal	Chipset	GMA900
	Memory Size	Share System Memory, 32 MB
	Resolution Size	15" TFT LCD / 1024 x 768
	Brightness	250 cd/m2 (Adjustable)
	Touch Screen	ELO 5-wire Resistive Touch
	Optional Peripherals	2-in-1 (MSR + Finger print)



Conectividad I/O	Serial Port	4 x External: COM1, COM2, COM5 (D-SUB9), COM6 (RJ-45) 2 x Internal: COM3 for Touch Screen, COM4 for VFD.
	Parallel Port	1 x Bi-directional Parallel (D-SUB25)
	Standard USB Port	7 x USB 2.0 - 3 x internal - 4 x external Front side x 1. Rear side x 4 (12 v.Power USB X1, 5V Power USB X1)
	Audio Port	Line-out
	Cash Drawer Port	1 x 12V / 24V Cash Drawer RJ11 connector (single / dual)
	PS/2 Keyboard Port	N / A (for Optional peripherals only)
	Ethernet	1 x RJ45 10/100/1000 Base-T



Display lado Cliente (Optional)	LCD Display	15" TFT LCD (Resistive Touch / Non Touch)
	VFD	VFD Display

Características	Dimensions (W x H x D)	379,40 x 386,60 x 300,00 mm.
	Housing Color	Silver, Black, Blue/Silver, Red/Black, Silver/Black
	Weight	14Kg (include one VFD)
	OperatingTemperature	0° ~ 35°
	Power Supply	120W 19 V Adapter
	EMI / Safety	CE, FCC, UL, RoHS

